



Best aid
SAFETY WAY

ISO-9001

TSB

MOST SUITABLE FOR VERTICAL MACHINE CENTER

最適合立式綜合切削加工機，銑床使用

MODEL • 07712130 TSB-130T • 07712200 TSB-200T
• 07712160 TSB-160T

MODEL • 07714100 TSB-100U • 07714160 TSB-160U
• 07714130 TSB-130U • 07714200 TSB-200U



0 ~ 45°



0 ~ 45°

0 ~ 360°

EXAMPLE A / 範例 A (0~45°)




0~45°

The T-slot on table could fasten the work piece to carry out 0~45° and 2 dimension angle machining.

工作台面上T型槽，可以直接固定工件，亦可裝上虎鉗做0~45°斜度加工，可以達2度空間角度加工。

EXAMPLE B / 範例 B (0~45°+0~360°)



0~45°

This type can only be fitted with vise for 0~45° tilt adjustment. The vise can be tuned from 0~360° to perform 3 dimension angle work.
此種型式只能裝上虎鉗，其可以0~45°做傾斜調整，其虎鉗亦可0~360°角度任意調整，以達3度空間角度加工。

FEATURES :

- Suitable for MC machining center, milling machine, EDM and other special machines to carry out tilt processing operation.
- Slant degree is between 0~45°. Angle can be fine tuned with worm and worm gear.
- Each fine-tuning scale equals 2 degree. The smallest scale is 60 seconds with another 1/60-second marks on the secondary scale.
- The body is made of steel with high rigidity. Sliding surface is heat treatment and processed with fine grinding.
- Once the tuning is fixed and properly fastened, heavy duty can be performed. There will be no loss of accuracy caused by heavy duty work.
- This universal tilt working table can be categorized into two types:
A) Working table with T-slot which can lock work piece for heavy duty machining. (0~45° adjustable angle)
B) Working table which can be in-cooperated with vise for heavy duty machining. (Adjustable 0~45° working table and 0~360° vise rotary angle)


特性:

- 適用於MC綜合切削加工機、銑床、放電加工機，或其他特殊機械做傾斜加工用。
- 傾斜角度可從0~45°任意調整，角度調整設計有渦桿、渦輪，可微調精密角度。
- 微調刻劃每一圈為 2° ，最小刻劃為1分，副尺再刻有60秒。
- 整台剛性結構極佳，並全部採用鋼材製造，滑動面經熱處理，精密研磨。
- 角度微調並鎖定之後，可做重切削加工，其精度不因重切削而使角度精度流失。
- 本萬能傾斜工作台分兩種型式：
A.工作台設有T型槽，可將工件直接固定在工作台面，直接做重切削加工。(調整角度0~45°)。
B.工作台面可直接連結協威製虎鉗來夾緊工件，來做重切削加工。(調整角度0~45°，虎鉗迴轉角度0~360°)。

MC TILT TABLE (WHOLE STEEL)

MC 精密型 / 傾斜工作台 (全鋼製)


OPERATION / 角度調整使用說明圖例:



MODEL • 07712130 TSB-130T • 07712200 TSB-200T
• 07712160 TSB-160T

This model can fasten the work piece directly on to the working table and carry out 0~45° machining. It can be cooperated with vise which can't be adjusted within 0~360°.

此機種可直接工件固定工作台面上，作傾斜0~45°加工，亦可裝上虎鉗，但虎鉗不可作0~360°角度調整。




Standard Accessories
1.17mm Wrench x 1 pc
2.14mm Handle x 1 pc
3.Locked block x 4 pcs

標準附件

1.17mm L型扳手 x 1 支
2.14mm 回轉把手 x 1 支
3.固定塊 x 4 只

MODEL • 07714100 TSB-100U • 07714160 TSB-160U
• 07714130 TSB-130U • 07714200 TSB-200U

This model must be fitted with vise made by Safeway. Working table can be tilted 0~45° degree and vise can be turned around 0~360° degree.
此機種必須裝上協威所製系列虎鉗於工作台面，工作台可從0~45°傾斜，虎鉗亦可0~360°任意迴轉。

**Standard Accessories**

1.17mm wrench x 1 pc
2.14mm handle x 1 pc
3.Fixed screw x 4 pcs
4.0~360° Swivel plate for Fixed vise x 2 pcs
5.T-Bolt x 4 pcs
6.T-Nut x 4 pcs

標準附件

1.17mm L型扳手 x 1 支
2.14mm 回轉把手 x 1 支
3.固定塊 x 4 只
4.虎鉗0~360°
迴轉壓塊 x 2 只
5.迴轉壓塊T型螺栓 x 4 只
6.迴轉壓塊用螺帽 x 4 支

Unit: mm

| Order NO. 訂購編號 | Model 型號 | A | B | C | D | H | I | J | K | L | T | Title angle 傾斜角 | N.W. 淨重 | G.W. 毛重 | Shipment Size 裝箱尺寸 | Remark 備 註 |
|-------------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|--------------------|------------|------------|-----------------------|---------------|
| 07712130 | TSB-130T | 200 | 196 | 300 | 180 | 122 | 127 | 192 | 270 | 18 | 16 | 0~45° | 30kg | | | |
| 07712160 | TSB-160T | 250 | 240 | 350 | 230 | 150 | 155 | 236 | 320 | 18 | 18 | 0~45° | 55kg | | | |
| 07712200 | TSB-200T | 290 | 280 | 410 | 255 | 174 | 179 | 274 | 370 | 18 | 18 | 0~45° | 88kg | | | |

| Order NO. 訂購編號 | Model 型號 | A | B | C | D | H | I | J | K | M | Title angle 傾斜角 | Swivel angle 迴轉角 | N.W. 淨重 | G.W. 毛重 | Shipment Size 裝箱尺寸 | Remark 備 註 |
|-------------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|----|--------------------|---------------------|------------|------------|-----------------------|---------------|
| 07714100 | TSB-100U | 200 | 196 | 300 | 180 | 122 | 127 | 192 | 270 | 16 | 0~45° | 0~360° | 38kg | | | |
| 07714130 | TSB-130U | 200 | 196 | 300 | 180 | 122 | 127 | 192 | 270 | 18 | 0~45° | 0~360° | 38kg | | | |
| 07714160 | TSB-160U | 250 | 240 | 350 | 230 | 150 | 155 | 236 | 320 | 18 | 0~45° | 0~360° | 58kg | | | |
| 07714200 | TSB-200U | 290 | 280 | 410 | 255 | 174 | 179 | 274 | 370 | 18 | 0~45° | 0~360° | 90kg | | | |